# **Industrial Scales**



# Cruiser<sup>®</sup> CKT Bench Checkweighing Scales

Ideal for inventory control or packaging tasks, saving money by reducing waste and overages



#### **General Specifications**

- Capacity: 4kg to 48kg
- Readability: 0.05g to 0.01kg · Weighing units: g, kg, lb, lb:oz, oz
- Power Supply: 12VDC 800mA
- adapter, Internal rechargeable battery Display: Backlit LCD with
- 15mm-high digits
- Calibration: External
- Housing: ABS plastic
- Operating Temperature: -10° to 40°C
- Pan Size: 300x210mm

#### Cruiser<sup>®</sup> CCT Bench Counting Scales

Intelligent functions for shipping and receiving, warehouse use, and production facilities



- · Readability: 0.1g to 0.5g
- · Weighing units: g, kg, lb
- Power Supply: 12VDC 800mA
- adapter, Internal rechargeable battery Display: Backlit LCD with
- 15mm-high digits
- Calibration: External
- Housing: ABS plastic
- Operating Temperature: -10° to 40°C
- Pan Size: 300x210mm

### **CPWplus Bench and Floor Scales**

Simple to operate and versatile, offering multiple configurations to suit numerous applications



#### **General Specifications**

- Capacity: 6kg to 200kg
  - Readability: 0.002kg to 0.05kg • Weighing units: kg, lb, lb:oz, oz
  - Interface: RS-232
  - Power Supply: 12VDC 500mA adapter, 6 xAA batteries
  - Display: Backlit LCD with
  - 22mm-high digits
  - Calibration: External
  - Housing: Mild steel base with aluminium extrusion display
  - Operating Temperature: 0° to 40°C
  - Pan Size: 300x300mm

# **GBK & GFK Bench and Floor Scales**

Ideal for industrial settings, when needing heavy-duty durability and speed. Available in Standard and Plus set-ups

#### General Specifications Capacity: 8kg to 600kg

- Readability: 0.1g to 50g
- Weighing units: g, kg, lb, lb:oz, oz • Power Supply: Power cord, Internal
- rechargeable battery (optional extra on standard models)
- · Display: Backlit LCD with 40mm-high digits
- Calibration: External
- Housing: ABS plastic indicator with mild steel base
- Operating Temperature: -10° to 40°C Pan Size: 400x300mm, 500x400mm, 800x600mm

# CPWplus M & L Bench and Floor Scales

Superb performance and simple to use operation for demanding tasks



#### **General Specifications**

- Capacity: 35kg to 300kg
- · Readability: 0.01kg to 0.1kg
- Weighing units: kg, lb, lb:oz, oz
- Interface: RS-232
- Power Supply: 12VDC 800mA adapter, Internal rechargeable battery
- Display: Backlit LCD with
- 22mm-high digits
- Calibration: External
- Housing: Mild steel base with aluminium extrusion display
- Operating Temperature: 0° to 40°C
- Pan Size: 500x500mm (M),
- 900x600mm (L)

#### GFC Checkweighing Floor Scales

Delivering power and efficiency needed to count large quantities of oversized items



# **General Specifications**

- · Power Supply: Mains power cord,
- Internal rechargeable battery
- · Display: Backlit LCD with 20mm-high digits
- Calibration: External
- · Housing: ABS Plastic indicator with mild steel base
- Operating Temperature: -10° to 40°C Pan Size: 500x400mm

# adameguipment.com.au

# **Industrial Scales**



# **BCT Label-Printing Counting Scales**

Built-in printer facilitates heavy-duty industrial counting tasks

AELP Pallet Beam Scales with GK Indicator

facilitate safe, secure weighing for loaded pallets

Rugged built and ideal for measuring oversized items,



#### **General Specifications**

- · Capacity: 16kg to 300kg
- · Readability: 0.5g to 20g
- Weighing units: g, kg, lb, oz
- Interface: RS-232
- Power Supply: 12VDC 3A adapter, 10Ah Internal rechargeable battery
- · Display: Backlit LCD with
- 22mm-high digits
- Calibration: External
- · Housing: ABS plastic indicator with mild steel base
- Operating Temperature: -10° to 40°C
- Pan Size: 400x300mm, 500x400mm
- (BCT 75, 150, 300)

# **BKT Label-Printing Scales**

Sturdy and durable, quickly producing custom labels and barcodes with the built-in printer



#### **General Specifications**

- · Capacity: 8kg to 600kg
- Readability: 0.1g to 50g • Weighing units: g, kg, lb, lb:oz, oz
- Interface: RS-232
- Power Supply: 12VDC 3A adapter, 10Ah Internal rechargeable battery
- · Display: Backlit LCD with 34mm-high digits
- Calibration: External
- Housing: ABS plastic indicator
- with mild steel base Operating Temperature: -10° to 40°C
- Pan Size: 400x300mm, 500x400mm (BCT 75, 150, 300) and 800x600mm (BKT 600)

### PT Industrial Platform Scales with GK Indicator

Durability and quality construction for ultimate performance



#### **General Specifications**

- Capacity: 1000kg to 3000kg
- · Readability: 0.2kg to 1kg
- Weighing units: g, kg, lb, lb:oz, oz, N
- Interface: RS-232, optional USB Power Supply: 12VDC 800mA adapter,
  - Internal rechargeable battery
- Display: Backlit LCD with
- 40mm-high digits
- Calibration: External
- Housing: Mild steel base
- Operating Temperature: -10° to 40°C
- Beam Size: 1330x120mm

# **PTSplus Pallet Truck Scales**

Heavy-duty reinforced steel pallet forks are an easy way to manage, move and weigh heavy loads

#### **General Specifications**

- Capacity: 2000kg
- Readability: 0.5kg
- Weighing units: kg, lb, lb:oz, oz, N Interface: RS-232
- Power Supply: Fixed mains power cord,
- Internal rechargeable battery
- · Display: Backlit LCD with 40mm-high digits
- Calibration: External
- Housing: Mild steel base
- Operating Temperature: -10° to 40°C
- Fork Size: 1200x160mm

# • Weighing units: kg, lb, lb:oz, oz, N Interface: RS-232, optional USB · Power Supply: 12VDC 800mA adapter,



**General Specifications** 

Capacity: 1000kg to 3000kg

Readability: 0.2kg to 0.5kg

- Display: Backlit LCD with
- 40mm-high digits
- Calibration: External
- Housing: Mild steel base
- Operating Temperature: -10° to 40°C Pan Size: 1000x1000mm (PT 110, 310), 1200x1200mm (PT 112, 312), 1500x1500mm (PT 115, 315)



# Supplied By:

# adameguipment.com.au



